

Tube OD Range

Model	Dash No.	Minimum	Inches	Maximum	Minimum	mm	Maximum
40	1.5	0.020	0.094	0.104	0.51	2.38	2.64
	2	0.115	0.125	0.135	2.92	3.18	3.43
	2.2	0.131	0.141	0.151	3.32	3.57	3.83
	2.5	0.146	0.156	0.166	3.72	3.97	4.22
	2.7	0.162	0.172	0.182	4.11	4.37	4.62
	3	0.178	0.188	0.198	4.51	4.76	5.02
	3.5	0.209	0.219	0.229	5.30	5.56	5.81
	3.6	0.215	0.225	0.235	5.46	5.72	5.97
	3.8	0.228	0.238	0.248	5.78	6.03	6.29
	4	0.240	0.250	0.260	6.10	6.35	6.60
	4.2	0.253	0.263	0.273	6.41	6.67	6.92
	4.4	0.265	0.275	0.285	6.73	6.99	7.24
	4.7	0.284	0.294	0.304	7.21	7.46	7.72
	5	0.303	0.313	0.323	7.68	7.94	8.19
	5.2	0.315	0.325	0.335	8.00	8.26	8.51
	5.5	0.334	0.344	0.354	8.48	8.73	8.99
	5.6	0.340	0.350	0.360	8.64	8.89	9.14
	5.7	0.346	0.356	0.366	8.80	9.05	9.30
	6	0.365	0.375	0.385	9.27	9.53	9.78
	6.2	0.378	0.388	0.398	9.59	9.84	10.10
	6.5	0.396	0.406	0.416	10.07	10.32	10.57
	6.8	0.415	0.425	0.435	10.54	10.80	11.05
7	0.428	0.438	0.448	10.86	11.11	11.37	
7.2	0.440	0.450	0.460	11.18	11.43	11.68	
7.5	0.459	0.469	0.479	11.65	11.91	12.16	
7.8	0.478	0.488	0.498	12.13	12.38	12.64	
41	8	0.490	0.500	0.510	12.45	12.70	12.95
	8.5	0.521	0.531	0.541	13.24	13.49	13.75
	9	0.553	0.563	0.573	14.03	14.29	14.54
	9.5	0.584	0.594	0.604	14.83	15.08	15.34
	10	0.615	0.625	0.635	15.62	15.88	16.13
42	11	0.678	0.688	0.698	17.21	17.46	17.72
	12	0.740	0.750	0.760	18.80	19.05	19.30
	13	0.803	0.813	0.823	20.38	20.64	20.89
	14	0.865	0.875	0.885	21.97	22.23	22.48
	15	0.928	0.938	0.948	23.56	23.81	24.07
	16	0.990	1.000	1.010	25.15	25.40	25.65